

Néon Max

Proven and validated by Domino Sign, Neon Max offers the best guarantees in terms of LED quality, envelope and colour rendering thanks to its anti-UV treatment.


Express your creativity with Max Neon divisible every 2.63 cm.

The electrical connection mode by soldering ensures a durable solution.

A system of 5 types of end caps guarantees the tightness and mechanical resistance of all connections.




- Homogeneous luminous flux (120 led/m)
- 180° angle
- IP 67
- Available in 7 colours
- Securable every 2.63 cm
- 4-year warranty



Néon Max



Néon Max								
	blanc / white 6500 K	blanc chaud / warm white 2500 K	jaune / yellow 573 nm	orange / orange 605 nm	rouge / red 615,5 nm	bleu / blue 464 nm	vert / green 521 nm	rose / pink pantone 233u
Flux lumineux / Luminous flux (lm)	545	284	584	584	230	461	517	390
Consommation / Consumption (W/m)	9,12	9,12	9,12	9,12	9,12	9,12	9,12	9,12
Animateur / Animation	oui / yes							
Gradateur / Dimmer	oui / yes							




Packaging - Warranty

Packaging: 40 m reel (4 x 10 m)

Service life: 40,000 hours

Warranty: 4 years for use from 8 to 10 hours a day

Silicone tips



Profile Néon

